

# LTIP2AB-36

2.0 Megapixel 1080P IP Armor Ball Camera



## Features

- 2.0Megapixel High Resolution
- H.264 & JPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC
- 3.6mm Fixed Lens
- 65ft IR (20m)
- IP66, External PoE



## Specifications

LTIP2AB-36	
Image Sensor	1080P / 2.0 Megapixel 1/2.9" Sony CMOS
Resolution	1920 x 1080
Frame Rate	30fps @1080P
Scanning System	Progressive
Electronic Shutter	1/50 ~ 1/10,000s
Focal Length	3.6mm
Lens Type / Control	Fixed
Min. Illumination   Color / B&W	0.01 Lux @ F1.2 (AGC On), 0 Lux with IR
Infrared Range	65ft / 20m
Day / Night	IR-CUT filter with Auto Switch
Wide Dynamic Range	DWDR
Backlight Compensation	AWB / AGC / BLC
Noise Reduction	3D-DNR
Privacy Masking	Up to 4 areas
Compression	H.264 / JPEG
Bit Rate	128 Kbps - 8 Mbps
Ethernet	1 x RJ45 Ethernet Port (10/100M Ethernet Interface)
Protocol	HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, DHCP, DNS, PPPoE
Compatibility	Supports standard ONVIF
Smart Phone	iPhone, iPad, Android
Weatherproof Rating	IP66
Power Supply	12V±10% DC
Current	w/o PoE: 150mA±15% (IR off), 275mA±15% (IR on) with PoE: 175mA±15% (IR off), 295mA±15% (IR on)
Storage Environment	-4°~158°F (-20°~70°C)
Operation Temperature	14°~122°F (-10°~50°C)
Dimensions / Weight	3.8" × 4.2" (96.9mm x 106mm) / Approx 0.8 lbs (360g)